SAMSUNG
ELECTRONICS

DATE : 06. Feb. 2012

SAMSUNG TFT-LCD

MODEL : LSJ320HN03

The Information Described in this Specification is Preliminary and can be changed without prior notice

LCD Business

Samsung Electronics Co . , LTD.

Contents

Revision History

Date	Rev. No	Page	Summary
06.Feb.2012	000	all	First issued

General Description

Description

 LSJ320HN03 is a color active matrix liquid crystal display (LCD) that uses amorphous silicon TFT(Thin Film Transistor) as switching components. This model is composed of a TFT LCD panel, a driver circuit. The resolution of a 32" is 1920 x 1080 and this model can display up to 1.07 billion colors with wide viewing angle of 89° or higher in all directions. This panel is intended to support applications to provide a excellent performance for Flat Panel Display such as Home-alone Multimedia TFT-LCD TV and High Definition TV.

Features

- High contrast & aperture ratio with wide color gamut
- SVA (Super Vertical Align) mode
- Wide viewing angle ($\pm$178°)
- High speed response
- FHD resolution (16:9)
- 2Ch LVDS (Low Voltage Differential Signaling) interface

General Information

Items	Specification	Unit	Note
Panel Size	715.4(H) x 411.8(V)	mm	$\pm$1.0mm
	1.76(D)		Max
Weight	1.2(Max)	kg	
Pixel Pitch	0.12125(H) X 0.36375(V)	mm	
Active Display Area	698.4(H) X 392.85(V)	mm	
Surface Treatment	Haze 2%, Hard-coating (2H)		
Display Colors	16.7M (8Bits Dithering)	colors	
Number of Pixels	1920 x 1080	pixel	
Pixel Arrangement	RGB vertical stripe		
Display Mode	Normally Black		

1. Absolute Maximum Ratings

If the condition exceeds maximum ratings, it can cause malfunction or unrecoverable damage to the device.

$(V_{SS} = 0\ V)$

Item		Symbol	Min.	Max.	Unit	Note
Power Supply Voltage		V_{DD}	10.8	13.2	V	(1)
Storage temperature		T_{STG}	5	40	℃	(2)
Glass surface temperature (Operation)	Center	T_{OPR}	0	50	℃	(2)

Note (1) Ta= 25 $\pm$ 2 °C
   (2) Temperature and relative humidity range are shown in the figure below.
      a. 90 % RH Max. (Ta ≤ 39 °C)
      b. Relative Humidity is 90% or less. (Ta > 39 °C)
      c. No condensation

| MODEL | LSJ320HN03 | Doc. No | 07-000- G-20120206 | Page | 5/24 |

2. Optical Characteristics

The optical characteristics should be measured in a dark room or equivalent.
Measuring equipment : TOPCON RD-80S, ELDIM EZ-Contrast

(Ta = 25 ± 2°C, VDD=12V)

| Item		Symbol	Condition	Min.	Typ.	Max.	Unit	Note
Contrast Ratio (Center of screen)		C/R		4,000	5,000	-		(1) D65
Response Time	G-to-G	Tg		-	8	16	msec	(3) RD-80S
Color Chromaticity (CIE 1931)	Red	Rx	Normal $\theta L,R=0$ $\theta U,D=0$ Viewing Angle	TYP. -0.03	0.640	TYP. +0.03		(5),(6) D65
		Ry			0.330			
	Green	Gx			0.300			
		Gy			0.600			
	Blue	Bx			0.150			
		By			0.060			
	White	Wx			0.280			
		Wy			0.290			
sRGB Concordance		-		-	98.5	-	%	(5) D65
Color Temperature		-		-	10,000	-	K	
Viewing Angle	Hor.	θ_L	C/R≥10	75	89	-	Degree	(6) EZ-Contrast
		θ_R		75	89	-		
	Ver.	θ_U		75	89	-		
		θ_D		75	89	-		

Notice

(a) Test Equipment Setup
    The measurement should be executed in a stable, windless and dark room between
    40min and 60min after operating the Panel at the given temperature for stabilization
    of the standard light(SEC use standard illuminant D65 Media).
    This should be measured in the center of screen.   Environment condition : Ta = 25 ± 2 °C

Photo detector	Field
SR3	1°
RD-80S	2°

Photo detector

Field

BM-5A : 50㎝
RD-80S : 50㎝
EZ-Contrast:0㎝

TFT - LCD Module

LCD Panel

The center of the screen

- Definition of test point

```
         320        960       1600

180     (9)        (8)        (7)          Active Area

540     (6)        (5)        (4)        ◯ Test Point

900     (3)        (2)        (1)
```

Note (1) Definition of Contrast Ratio (C/R)
    : Ratio of gray max (Gmax) & gray min (Gmin) at the center point ⑤ of the panel
    : The measurement goes in D65 Standard Light Source

$$C/R = \frac{G\max}{G\min}$$

    Gmax : Luminance with all pixels white
   Gmin : Luminance with all pixels black

Note (2) Definition of 9 points Transmittance uniformity (Test pattern : Full White)
        The measurement goes in D65 Standard Light Source

$$Tuni = \frac{(T\max - T\min)}{T\max} \times 100$$

Tmax : Maximum Transmittance
Tmin : Minimum Transmittance

Note (3) Definition of Response time : Sum of Tr, Tf

Display data	Black (data off)	White (data on)	Black (data off)

Optical Instruments Response
100%
90%
10%
0%
T_R T_F
TIME

※ G-to-G : Average response time between Gray to Gray (Scale)

Note (4) Definition of Transmittance : Transmittance of white at center point ⑤
        The measurement goes in D65 Standard Light Source

Note (5) Definition of Color Chromaticity (CIE 1931)
        Color coordinate of Red, Green, Blue & White at center point ⑤
        The measurement goes in D65 Standard Light Source

Note (6) Definition of Viewing Angle
        : Viewing angle range (C/R ≥10)
        The measurement goes in D65 Standard Light Source

Θ_U Θ_R Θ_L Θ_D

MODEL	LSJ320HN03	Doc. No	07-000- G-20120206	Page	8/24

3. Electrical Characteristics

3.1 TFT LCD Module

The connector for display data & timing signal should be connected.

Ta = 25°C ± 2 °C

Item		Symbol	Min.	Typ.	Max.	Unit	Note
Voltage of Power Supply		VDD	10.8	12.0	13.2	V	(1)
Current of Power Supply	(a) Black	IDD	-	500	700	Ma	(2),(3)
	(b) White		-	500	700	mA	
	(c) N-pattern		-	800	1000	mA	
Vsync Frequency		fV	47	60	63	Hz	
Hsync Frequency		fH	50	67.5	75	kHz	
Main Frequency		Fdclk	130	148.5	160	MHz	
Rush Current		IRUSH	-	-	4	A	(4)

Note (1) The ripple voltage should be controlled under 10% of V_{DD}.

(2) f_V= 60 Hz, f_{DCLK} = 148.5 MHz, V_{DD} = 12.0V, DC Current.

(3) Power dissipation check pattern (LCD Module only)

a) Black Pattern   b) White Pattern   c) N-pattern

(4) Measurement Conditions

T_{RUSH}=470μs

Rush Current I_{RUSH} can be measured when T_{RUSH}. is 470μs.

4. Input Terminal Pin Assignment

4.1. Input Signal & Power

Pin	Description			Pin	Description		
1	Vdd (12V)			26		Rx3[0]P	
2	Vdd (12V)			27		Rx3[1]N	
3	Vdd (12V)			28		Rx3[1]P	
4	Vdd (12V)			29		Rx3[2]N	
5	Vdd (12V)			30		Rx3[2]P	
6	N.C			31	Even	GND	
7	GND			32	LVDS	Rx3CLK-	
8	GND			33	Signal	Rx3CLK+	
9	GND			34		GND	
10		Rx1[0]N		35		Rx3[3]N	
11		Rx1[0]P		36		Rx3[3]P	
12		Rx1[1]N		37		Rx3[4]N	NOTE3
13		Rx1[1]P		38		Rx3[4]P	NOTE3
14		Rx1[2]N		39	GND		
15	Even	Rx1[2]P		40	No connection		
16	LVDS	GND		41	No connection		
17	Signal	Rx1CLK-		42	No connection		
18		Rx1CLK+		43	No connection		
19		GND		44	No connection		
20		Rx1[3]N		45	No connection		
21		Rx1[3]P		46	No connection		
22		Rx1[4]N	NOTE3	47	No connection		
23		Rx1[4]P	NOTE3	48	No connection		
24		GND		49	No connection		
25	Even LVDS	Rx3[0]N		50	No connection		
				51	No connection		

Note 1) NOT CONNECTED : THIS PINS ARE ONLY USED FOR SEC INTERNAL OPERATIONS.

Note 2) IF LVDS 8Bit Input

MODEL	LSJ320HN03	Doc. No	07-000- G-20120206	Page	10/24

Note(1) Pin number starts from Bottom side

PCB

#1 ▼   #51

#1   #51

Fig. Connector diagram

a. Power GND pins should be connected to the LCD's metal chassis.
b. All power input pins should be connected together.
c. All NC pin should be separated from other signal or power.

| MODEL | LSJ320HN03 | Doc. No | 07-000- G-20120206 | Page | 11/24 |

4.2 LVDS Interface
    - LVDS Receiver : Tcon (merged)   - Data Format (JEIDA)

	LVDS pin	JEIDA -DATA
TxOUT/RxIN0	TxIN/RxOUT0	R2
	TxIN/RxOUT1	R3
	TxIN/RxOUT2	R4
	TxIN/RxOUT3	R5
	TxIN/RxOUT4	R6
	TxIN/RxOUT6	R7
	TxIN/RxOUT7	G2
TxOUT/RxIN1	TxIN/RxOUT8	G3
	TxIN/RxOUT9	G4
	TxIN/RxOUT12	G5
	TxIN/RxOUT13	G6
	TxIN/RxOUT14	G7
	TxIN/RxOUT15	B2
	TxIN/RxOUT18	B3
TxOUT/RxIN2	TxIN/RxOUT19	B4
	TxIN/RxOUT20	B5
	TxIN/RxOUT21	B6
	TxIN/RxOUT22	B7
	TxIN/RxOUT24	HSYNC
	TxIN/RxOUT25	VSYNC
	TxIN/RxOUT26	DEN
TxOUT/RxIN3	TxIN/RxOUT27	R0
	TxIN/RxOUT5	R1
	TxIN/RxOUT10	G0
	TxIN/RxOUT11	G1
	TxIN/RxOUT16	B0
	TxIN/RxOUT17	B1
	TxIN/RxOUT23	RESERVED

4.3 Input Signals, Basic Display Colors and Gray Scale of Each Color

COLOR	DISPLAY (8bit)	RED R0	R1	R2	R3	R4	R5	R6	R7	R8	R9	GREEN G0	G1	G2	G3	G4	G5	G6	G7	G8	G9	BLUE B0	B1	B2	B3	B4	B5	B6	B7	B8	B9	GRAY SCALE LEVEL
BASIC COLOR	BLACK	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	-
	BLUE	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	-
	GREEN	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	-
	CYAN	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	-
	RED	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	-
	MAGENTA	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	-
	YELLOW	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	-
	WHITE	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	-
GRAY SCALE OF RED	BLACK	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R0
	DARK ↑	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R1
		0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R2
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	R3~ R1020
	↓	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	
	LIGHT	1	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R1021
		0	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R1022
	RED	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R1023
GRAY SCALE OF GREEN	BLACK	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	G0
	DARK ↑	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	G1
		0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	G2
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	G3~ G1020
	↓	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	
	LIGHT	0	0	0	0	0	0	0	0	0	0	1	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	G1021
		0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	G1022
	GREEN	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	G1023
GRAY SCALE OF BLUE	BLACK	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	B0
	DARK ↑	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	B1
		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	B2
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	B3~ B1020
	↓	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	
	LIGHT	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	1	1	1	1	1	1	1	1	B1021
		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	B1022
	BLUE	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	B1023

Note) Definition of Gray :

Rn : Red Gray, Gn : Green Gray, Bn : Blue Gray (n = Gray level)

Input Signal : 0 = Low level voltage, 1 = High level voltage

MODEL	LSJ320HN03	Doc. No	07-000- G-20120206	Page	13/24

5. Interface Timing

5.1 Timing Parameters (Timing-Controller)

SIGNAL	ITEM	SYMBOL	MIN.	TYP.	MAX.	Unit	NOTE
Clock	Frequency	$1/T_C$	130	148.5	160	MHz	
Frame Frequency	Cycle	T_V	45	60	65	Hz	
		T_H	48	67.5	75	KHz	
Vertical Display Term	Active Display Period	T_{VD}	-	1080	-	Lines	
	Vertical Total	T_{VB}	1092	1125	1158	Lines	
Horizontal Display Term	Active Display Period	T_{HD}	-	1920	-	Clocks	
	Horizontal Total	T_H	2090	2200	2350	Clocks	

Note) This product is DE only mode. The input of Hsync & Vsync signal does
not have an effect on normal operation.
(1) Test Point : TTL control signal and CLK at LVDS Tx input terminal in system
(2) Internal V_{DD} = 3.3V
(3) Spread spectrum
- Modulation rate (max) : $\pm$ 1.5 %
- Modulation Frequency : 30 ~ 300KHz

5.2 Timing diagrams of interface signal (DE only mode)

5.3 Power ON/OFF Sequence

To prevent a latch-up or DC operation of the LCD Module, the power on/off
sequence should be as the diagram below.

0.5ms<T1≤10ms
1ms<T2≤50ms
0ms<T3≤50ms
1000ms≤T4

1000ms≤T5

100ms≤T6

T1 : V_{DD} rising time from 10% to 90%
T2 : The time from V_{DD} to valid data at power ON.
T3 : The time from valid data off to V_{DD} off at power Off.
T4 : V_{DD} off time for Windows restart
T5 : The time from valid data to B/L enable at power ON.
T6 : The time from valid data off to B/L disable at power Off.

- The supply voltage of the external system for the Module input should be the same
  as the definition of V_{DD}.
- Apply the lamp voltage within the LCD operation range. When the back light turns on
  before the LCD operation or the LCD turns off before the back light turns off,
  the display may momentarily show abnormal screen.
- In case of V_{DD} = off level,
  please keep the level of input signals low or keep a high impedance.
- T4 should be measured after the Module has been fully discharged between power off
  and on period.
- Interface signal should not be kept at high impedance when the power is on.

6. Outline Dimension

| MODEL | LSJ320HN03 | Doc. No | 07-000- G-20120206 | Page | 17/24 |

7. PACKING

7.1 CARTON (Internal Package)

 (1) Packing Form Corrugated fiberboard box and corrugated cardboard as shock absorber
 (2) Packing Method

Packing- Upper Box

Pallet Tray

10EA   10EA

15EA

Pallet-Plastic

7.2 Packing Specification

| ITEM	Specification	Remark
LCD Packing	300ea / Box	1. 1.20 Kg / LCD (15[ea]/Tray, 300[ea]/Pallet) 2. 0.04 Kg / Middle sheet (16[ea]/Tray, 320[ea]/Pallet) 3. 2.00 Kg / Panel tray-Bottom (20ea/Pallet) 4. 0.50 Kg / Palel tray-Top (2ea)
Pallet-Wood	1Box / Pallet	1. 23 Kg / Pallet-Plastic (1ea) 2. 2.00 Kg / Packing Pallet-Box(1ea)
Pallet size	H x V x height	1,475mm(H) x 1,150mm(V) x 1,131mm(height)
Pallet weight	440.2 kg	Pallet(23kg) + Panel tray(40kg) + Panel(360kg) + Middle sheet(14.2Kg) + Packing Box (3kg)

8. MARKING & OTHERS

A nameplate bearing followed by is affixed to a shipped product at the specified location on each product.

### (1) Cell Label

Lot number : X X X X XXX XX X

- Cell Position No. (In the Glass)
- Glass No. (In the one Lot)
- Lot No. (Glass)
- Month
- Year (Note1)
- Product code
- Line

| MODEL | LSJ320HN03 | Doc. No | 07-000- G-20120206 | Page | 19/24 |

(2) Box Label

DVC : **LSJ320HN03**
TYPE : **xxxx**
QTY : **300**

ZAT93L1242

ZAT93L12420901

100mm

150mm

BOX Serial : X X X X X X XXXX XX XX

- Week
- Year
- Box No.
- Day
- Month
- Year
- Site
- Module Line
- Product Type

MODEL	LSJ320HN03	Doc. No	07-000- G-20120206	Page	20/24

9. General Precautions

9.1 Handling

(a) When the Module is assembled, it should be attached to the system firmly using all mounting holes. Be careful not to twist and bend the Module.

(b) Refrain from strong mechanical shock and / or any force to the Module. In addition to damage, this may cause improper operation or damage to the Module and CCFL back light.

(c) Note that polarizers are very fragile and could be damage easily. Do not press or scratch the surface harder than a HB pencil lead.

(d) Wipe off water droplets or oil immediately. If you leave the droplets for a long time, staining or discoloration may occur.

(e) If the surface of the polarizer is dirty, clean it using absorbent cotton or soft cloth.

(f) Desirable cleaners are water, IPA(Isopropyl Alcohol) or Hexane. Do not use Ketone type materials(ex. Acetone), Ethyl alcohol, Toluene, Ethyl acid or Methyl chloride. It might permanent damage to the polarizer due to chemical reaction.

(g) If the liquid crystal material leaks from the panel, it should be kept away from the eyes or mouth . In case of contact with hands, legs or clothes, it must be washed away with soap thoroughly.

(h) Protect the module from Electrostatic discharge. Otherwise the ASIC IC or Semiconductor would be damaged.

(i) Use finger-stalls with soft gloves in order to keep display clean during the incoming inspection and assembly process.

Peeling direction

a. Peel off slowly and constant speed
b. Be sure to ground S-PBA while peeling of the Protection film
c. The protection film must not touch drivers and S-PBAs

GND SR-OPEN Pattern
-Be sure to contact with ground
While Peeling of the protection film

(k) Protection film for polarizer on the Module should be slowly peeled off just before use so that the electrostatic charge can be minimized. Must put on antistatic glove while handle a module

(l) Pins of I/F connector should not be touched directly with bare hands.

* Process Control Standard

	Item	Management standard value and performance standard
1	Anti-static mat (shelf)	1 to 50 [Mohm]
2	Anti-static mat (floor, desk)	1 to 100 [Mohm]
3	Ionizer	Attenuate from $\pm$ 1,000V to $\pm$ 100V within 2 sec
4	Anti-static wrist band	0.8 to 10 [Mohm]
5	Anti-static wrist band entry and ground resistance	Below 1,000 [ohm]
6	Temperature	0 ~ 35℃
7	Humidity	60 to 70 [%RH]

9.2 Storage

We highly recommend to comply with the criteria in the table below

ITEM	Unit	Min.	Max.
Storage Temperature	(℃)	5	40
Storage Humidity	(%rH)	35	75
Storage life	6 months		
Storage Condition	- The storage room should provide good ventilation and temperature control. - Products should not be placed on the floor, but on the Pallet away from a wall. - Prevent products from direct sunlight, moisture nor water; Be cautious of a build up of condensation. - Avoid other hazardous environment while storing goods.		

After	1 month	2 month	3 month	4month	5 month	6month
Baking	No backing		50℃ 10% 24Hr	50℃ 10% 48Hr		

9.3 Operation

(a) Do not connect or disconnect the Module in the "Power On" condition.

(b) Power supply should always be turned on/off by the "Power on/off sequence"

(c) Module has high frequency circuits. Sufficient suppression to the electromagnetic interference should be done by system manufacturers. Grounding and shielding methods may be important to minimize the interference.

(d) The cable between the back light connector and its inverter power supply should be connected directly with a minimized length. A longer cable between the back light and the inverter may cause lower luminance of lamp(CCFT) and may require higher startup voltage(Vs).

9.4 Operation Condition Guide

(a) The LCD product should be operated under normal conditions.
  Normal condition is defined as below;
    - Temperature : $20\pm15℃$
    - Humidity : $55\pm20\%$
    - Display pattern : continually changing pattern (Not stationary)

(b) If the product will be used in extreme conditions such as high temperature,
  humidity, display patterns or operation time etc.., It is strongly recommended
  to contact SEC for Application engineering advice. Otherwise, its reliability and
  function may not be guaranteed. Extreme conditions are commonly found at
  Airports, Transit Stations, Banks, Stock market, and Controlling systems.

9.5 Others

(a) Ultra-violet ray filter is necessary for outdoor operation.

(b) Avoid condensation of water. It may result in improper operation or disconnection
  of electrode.

(c) Do not exceed the absolute maximum rating value. (supply voltage variation,
  input voltage variation, variation in part contents and environmental temperature,
  and so on)
  Otherwise the Module may be damaged.

(d) If the Module keeps displaying the same pattern for a long period of time,
  the image may be "sticked" to the screen.
  To avoid image sticking, it is recommended to use a screen saver.

(e) This Module has its circuitry PCB's on the rear side and should be handled
  carefully in order not to be stressed.

(f) Please contact SEC in advance when you display the same pattern for a long time.